



The
Patent
Office

07 MAY 1999

PCT/GB 99 / 0 1 4 3 1
1999



INVESTOR IN PEOPLE

EATU

09/674902

The Patent Office
Concept House
Cardiff Road
Newport
South Wales

GB99/1431

NP10 8QQ	
REC'D 07 JUL 1999	
WIPO	PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.


**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)


Signed

Dated

23 JUN 1999



THIS PAGE BLANK (USPTO)



The
Patent
Office

1/77
11MAY98 E359220-1 D00239
P01/7700 25.00 - 9809885.8

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference

SK/P08234GB

09 MAY 1998

2. Patent application number

(The Patent Office will fill in this part)

9809885.8

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Vircon Limited
Level 2, Saltire Court
20 Castle Terrace
Edinburgh EH1 2ET

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

Scotland, UK

7434300061

4. Title of the invention

PROTECTED STORAGE DEVICE FOR COMPUTER SYSTEM

5. Name of your agent (if you have one)

CRUIKSHANK & FAIRWEATHER

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

19 Royal Exchange Square
Glasgow G1 3AE
United Kingdom

Patents ADP number (if you know it)

547002 ✓

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

Yes

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body.

See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form	-
Description	27
Claim(s)	-
Abstract	-
Drawing(s)	2 + 2

10. If you are also filing any of the following, state how many against each item.

Priority documents	-
Translations of priority documents	-
Statement of inventorship and right to grant of a patent (Patents Form 7/77)	-
Request for preliminary examination and search (Patents Form 9/77)	-
Request for substantive examination (Patents Form 10/77)	-
Any other documents (please specify)	-

11.

I/We request the grant of a patent on the basis of this application.

C. Smith & Partners
Signature (Agents)

Date 08/05/1998

12. Name and daytime telephone number of person to contact in the United Kingdom

Sheila A F Kerr

0131 228 2992

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

PROTECTED STORAGE DEVICE FOR COMPUTER SYSTEM

The present invention relates to a method and apparatus for controlling access to and corruption of information in a
5 computer system.

US 5,657,473 discloses a method and apparatus particularly concerned with the detection and containment of hostile programs such as "virus" programs within computer systems,
10 said method including dividing the information stored on the storage medium into a plurality of non-overlapping partitions, including a boot partition and a plurality of general partitions, each of the partitions being further divided into a plurality of sectors, any designated subset of the general
15 partitions being active at any given time when the computer system is in use,
said invention employing a supervising means (a Supervisor) separate of the central processing unit (CPU)
allowing/restricting/prohibiting read/write operations upon
20 the storage medium depending on whether information to be read from a sector or written to a sector is in the boot partition, or in a general partition, and whether the partition is active or inactive, and

-2-

said supervising means also allowing a format operation only on a partition which is active and prohibiting a format operation on the boot partition, or on a general partition if it is inactive.

5

The described invention preferably uses a second processor which is made inaccessible to the user and to the virus, supervising all data transfers between and within subdivisions of the device or devices placed under its control.

10

The Patent Application describes, as an example, an embodiment comprising a printed circuit board assembly containing a dedicated micro-controller, used in place of the hard disk controller within the computer system.

15

EP 0 800 135 A1 discloses a method and apparatus for controlling access to and modification of information stored on a storage medium forming part of a computer system, said invention including by reference all aspects of the

20 aforesaid invention of US 5,657,473,

said invention designating at least one partition a Write Many Recoverable (WMR) partition wherein, in use, if a write command is issued to overwrite any resident information stored in a/the WMR partition by updated information, the updated

-3-

information is written on the storage medium in a location other than where any resident information is stored and a (virtual) pointer to the updated information is stored in a Sector Relocation Table (SRT) so that the updated information 5 can be accessed, as required during the remainder of a (user) session. An alternative method is also described wherein, if a write command is issued to overwrite any resident information stored in a/the WMR partition, prior to undertaking said write command said information is copied and stored elsewhere on the 10 storage medium to be copied back to said WMR partition when required. This could be implemented, for example, by a system reset.

The application describes, as an example, an embodiment 15 comprising a printed circuit board assembly (PCBA) containing a dedicated micro-controller placed in-line between the computer system hard disk drive controller (often embedded within the computer system motherboard) and the hard disk drive.

20

The method and apparatus in the aforementioned inventions propose the use of a second processor separate from the computer system central processing unit (CPU). Although the aforesaid inventions do not specifically limit their scope to

-4-

combined hardware and firmware embodiments, both describe in detail embodiments which include a separate printed circuit board assembly, placed between the CPU and the storage medium.

Such hardware embodiments have the following disadvantages:

5 Such hardware embodiments have an associated cost per unit, which results in a base cost for the invention which must be met irrespective of sales volume;

Such hardware embodiments must be installed within the computer system, generally requiring the computer system case
10 to be removed;

Such hardware embodiments require safety and emission approvals and require a high level of testing to ensure compatibility across the wide spectrum of existing computer systems;

15 Such hardware embodiments are subject to a level of component failures.

It is the subject of the present invention to avoid or minimise one or more of the aforesaid disadvantages. This
20 document discloses a method (and related apparatus for) incorporating the methods outlined in both US 5,657,473 and EP
0 800 135 A1 into the storage device itself.

-5-

Storage devices are frequently intelligent containing their own processor module, this being a potential candidate to undertake the functions of a Supervisor as described within the aforesaid inventions. This intelligent module controls the transfer of information to and from the storage medium via the interface to the computer system. According to the present invention as defined herebelow, this intelligent module is used to allow/restrict/prohibit, read/write operations upon the storage medium in a manner consistent with the aforesaid inventions.

According to a first aspect of the invention we provide a storage device for a host computer system, the storage device comprising: storage means for storing information; intelligent means for controlling the transfer of information to and from the storage means; and interfacing means for interfacing the storage device with the host computer system and via which information is transferred to and from the storage means under the control of said intelligent means,

the storage means comprising: a storage medium divided into a plurality of non-overlapping partitions; non-volatile read-only-memory (ROM) means for storing firmware for controlling operation of the storage device; and volatile random-access-memory (RAM) means;

-6-

wherein supervising means is incorporated in said storage means for operating said intelligent means so as to protect information stored in the storage medium.

5 The term "information" as used herein is intended to cover information, data and/or program code, any or all of which may be stored in the storage means.

The supervising means ("Supervisor") preferably protects the
10 said information by controlling access to and modification thereof in accordance with pre-programmed protection criteria.

Incorporating the Supervisor within the storage device has the following advantages:

15 where an intelligent means is already present on the storage device, the methods outlined in the aforesaid inventions may be implemented with no hardware changes to the storage device; physical installation of a separate PCBA containing the Supervisor is no longer required: Supervisor firmware may be
20 included within the storage device during manufacture or may be added by means of a software utility;
since a separate PCBA is no longer required, manufacturing costs are significantly reduced by removing the requirement for additional hardware components and no additional safety or

-7-

emission testing is required over and above that required for the storage device without Supervisor firmware; by removing the requirement for additional circuitry external to the storage device, there is a reduction in the 5 compatibility issues that may arise from the diversity of computer systems and storage device combinations which are possible.

The storage device may be a hard disk drive. The storage 10 medium may comprise one or more disk platters. The supervising means is preferably provided as firmware which is stored in said non-volatile ROM on the storage device. The intelligent means preferably comprises a processor, often referred to as a micro-controller, which runs the Supervisor firmware stored in 15 the ROM means. Hard disk drives are now available which incorporate a printed circuit board assembly (PCBA) including a micro-controller for running programs stored in memory means provided on the PCBA. In such drives, this processor means may conveniently function as the micro-controller for use in the 20 present invention. The Supervisor firmware can be stored in non-volatile ROM provided on the PCBA.

Said non-overlapping partitions into which the storage medium is divided preferably include a boot partition and at least

-8-

one general partition, each said partition being divided into a plurality of sectors. The storage medium may have a plurality of general partitions defined thereon, any designated subset of which are active at any given time, in use of the computer system.

Preferably, the supervising means operates said intelligent means so as to allow/restrict/prohibit read/write operations upon the storage medium depending upon whether information to be read from a sector or written to a sector is operating system information or user information, whether the sector is in the boot partition or in a general partition and whether if the partition is a general partition the partition is active or inactive. The supervising means may also allow a format operation only on a general partition which is active and prohibit a format operation on the boot partition or on a general partition which is inactive.

It will be appreciated that the supervising means preferably also ensures that firmware stored on the ROM means of the storage device, which includes the firmware providing the supervisor means, is also protected in that a user, or a user program operating in the host computer system, does not have access to the ROM means (or the RAM means) of the storage

-9-

device itself and any firmware or other code stored therein is thus unalterable by the user or user program.

Optionally, the supervising means may cause a warning to be issued to the user should an attempt be made to perform a prohibited read, write or format operation.

At least one of said partitions of the storage device may comprise a Write Many Recoverable (WMR) partition wherein, in use, if a write command is issued to overwrite (i.e. update) any information stored in the WMR partition the updated information is stored elsewhere on the storage medium, preferably in a dedicated area of the storage medium, and a (virtual) pointer to the updated information kept so the updated information can be accessed as required during the remainder of the session, wherein a system reset causes the list of pointers to the updated information, and optionally the updated information itself, to be cleared.

Where such a WMR partition is provided, the or each said WMR partition preferably has a Sector Relocation Table (SRT) associated therewith which is held in said volatile RAM means of the storage device, each entry in a said SRT is a (virtual) pointer which defines the address of a range of sectors in the

-10-

WMR partition that have been updated and an address where the updated information is located, this location being within a dedicated area on the storage medium which is accessed only by the supervisor means.

5

Alternatively, at least one of said partitions of the storage device comprises a Write Many Recoverable (WMR) partition wherein, in use, if a write command is issued to overwrite (i.e. update) any information stored in a/the WMR partition 10 prior to undertaking said write command said information is copied and stored elsewhere on the storage medium to be copied back to said WMR partition when required. This could be implemented, for example, by a system reset.

15 Where the storage medium comprises at least one disk platter and a boot partition, said boot partition will include a disk boot sector. According to the present invention, the storage device may be provided with loader means and said supervising means may be adapted to intercept any request for the disk 20 boot sector, issued by the host computer system in use thereof, and supply said loader means to satisfy the request. The loader means is preferably configured to load or transfer a predetermined code segment, which is stored on the storage means, to a central processing unit (CPU) of the host computer

system to be executed by the computer system prior to (normal) operating system boot. This code segment may provide user prompts, and communication with the supervising means. The loader means is preferably provided in said non-volatile ROM of the storage device. Alternatively, said loader means may be provided in a reserved area on the storage medium, for example in one or more reserved tracks of a said disk platter of the storage device. This reserved area is preferably inaccessible to a user or user program (but is accessible to the Supervising means) whereby unauthorised alteration of the loader means is prevented.

The code segment may be provided in said non-volatile ROM means of the storage device or, preferably, in a reserved area of the storage medium which is also preferably inaccessible to a user or user program, but is accessible to the Supervising means, whereby unauthorised alteration of the code segment is prevented.

20 Optionally, the storage device may be placed in either "supervised" mode, in which the supervising means is active, or "unsupervised" mode in which the supervising means is not active. Said code segment, when executed, preferably provides user prompts which allow a user to select either "supervised"

-12-

mode, or by entry of a password select "unsupervised" mode.

The code segment is preferably constructed such that, subsequent to mode selection by the user, the code segment transfers and executes a boot program from the disk boot
5 sector of the storage medium which, in turn, initiates operating system boot (in the host computer system) The correct password (for comparison against a password input by a user) may be stored in said non-volatile ROM of the storage device or on the storage medium itself.

10

According to a second aspect of the invention we provide a computer system incorporating a storage device according to the above-described first aspect of the invention.

15 According to a third aspect of the invention we provide a method of controlling access to and modification of information stored on a storage medium of a storage device for incorporation in a host computer system wherein the storage device comprises storage means for storing information,
20 intelligent means for controlling the transfer of information to and from the storage means, and interfacing means for interfacing the storage device with the host computer system and via which information may be transferred to and from the storage means under the control of said intelligent means, and

-13-

the storage means comprises: a storage medium; non-volatile read-only-memory (ROM) means for storing firmware for controlling operation of the storage device; and volatile random-access-memory (RAM) means;

5 the method comprising the steps of:

dividing the storage medium into a plurality of non-overlapping partitions including a boot partition and at least one general partition, and dividing each said partition into a plurality of sectors;

10 providing supervising means in said storage means for operating said intelligent means so as to protect information stored in the storage medium; and
incorporating the storage device in a host computer system, and running the host computer system with the supervising
15 means operating said intelligent means so as to protect information stored in the storage medium.

Preferably said supervising means is provided for allowing/restricting/prohibiting read/write operations upon
20 the storage medium depending upon whether information to be read from a sector or written to a sector is operating system information or user information, whether the sector is in the boot partition or in a general partition and whether if the

-14-

partition is a general partition the partition is active or inactive,

said supervising means optionally also allowing a format operation only on a general partition which is active and
5 prohibiting a format operation on the boot partition or on a general partition which is inactive,

said supervising means being adapted to intercept each interface request from the host computer system to said storage device,

10 and the supervising means, preferably, causing a warning to be issued to the user should an attempt be made to perform a prohibited read, write or format operation which operation is prevented by the supervising means;

providing a loader means, said supervising means being adapted
15 to supply said loader means in response to any request, issued by the host computer system, for the disk boot sector of the boot partition; and executing the loader means by the central processing unit (CPU) of the computer system in place of the requested disk boot sector, the loader sector transferring a

20 code segment stored in the storage device, preferably in the storage medium thereof, into a RAM of the CPU for execution thereon, the code segment, when executed, initiating a user interface procedure, preferably in the form of user prompts, whereby a user may select one or more protection options;

-15-

and whereupon, subsequent to a said selection having been made by the user, said code segment transfers the disk boot program stored in the disk boot sector as originally requested and, in turn, executes the disk boot program which then initiates
5 operating system boot (in the host computer system).

Said selection of protection options preferably includes the option, by entering a predetermined password, of setting the storage device in "unsupervised mode" whereby interface
10 requests are not intercepted by the supervising means. The selection may also include the option of setting the storage device in "supervised" mode and further selecting one or more active partitions and/or of designating at least one of said partitions a Write Many Recoverable (WMR) partition wherein,
15 in use, if a write command is issued to overwrite any resident information stored in a/the WMR partition by updated information, the updated information is written on the storage medium in a location other than where any resident information is stored and a (virtual) pointer to the updated information
20 is set up/kept so that the updated information can be accessed, as required during the remainder of a session.

The method may further include storing a Sector Relocation Table (SRT) which contains the (virtual) pointers associated

-16-

with each said WMR partition in the volatile RAM means of the storage device.

Alternatively, the method may include the option of designating at least one of said partitions a Write Many Recoverable (WMR) partition wherein, in use, if a write command is issued to overwrite (i.e. update) any information stored in a/the WMR partition prior to undertaking said write command said information is copied and stored elsewhere on the storage medium to be copied back to said WMR partition when required. This could be implemented, for example, by a system reset.

Preferred embodiments of the invention will now be described by way of example only, and with reference to the accompanying drawings in which:-

Fig 1 is a schematic diagram of a hard disk drive according to one embodiment of the invention;

Fig.2 is a flow chart illustrating a modified operating boot sequence implemented in the hard disk drive of Fig.1.

Fig.1 shows a storage device in the form of a hard disk drive 1 for incorporating in a host computer system (not shown). The drive is of conventional form having one or more disk platters

-17-

2 mounted on a spindle motor drive mechanism on a printed circuit board assembly (PCBA) 3 having a ROM chip 4 containing firmware for controlling operation of the drive, and a RAM chip 5. The drive has an interface connector 6 which enables 5 interfacing of the disk drive 1 to the host computer system, via which interface connector information, including user information, operating system information, data and other programs, is transferred to and from the disk platter(s) 2. The PCBA 3 has a micro-controller 7 provided thereon which 10 runs the firmware contained in the ROM chip 4, accesses the RAM chip 5 and controls the transfer of information, data and/or programs to and from the disk platter(s) via the interface.

15 The firmware in the ROM includes "Supervisor" firmware for intercepting and validating each request to the hard disk (from the host computer system) in a manner previously described in US 5,657,473, the contents of which are therefore incorporated herein by reference. The operation of the disk 20 drive beneficially also includes a method of controlling access to and modification of information stored on the disk platter(s) of the drive utilising a Write Many Recoverable (WMR) partition (or partitions) as previously disclosed in EP

-18-

0 800 135 A1, the content of which is also therefore incorporated herein by reference.

Thus, the supervising means (Supervisor) forms part of the
5 hard drive itself, separate of a central processing unit (CPU)
of the host computer system and inaccessible to the user, the
supervising means controlling access to information stored on
the disk platter(s).

10 According to the described embodiment, the disk drive
operation provides a method giving the user the capability of
selecting either an "unsupervised" or "unprotected" mode
through entry of a password, or selecting a "supervised" or
"protected" mode with further selection of one or more active
15 partitions. To do this, a loader means in the form of a
virtual "loader sector" is provided in the form of executable
code stored in the non-volatile ROM chip 4, the loader sector
acting as a replacement for the disk boot sector of the active
partition on the storage device, whereby each request (by the
20 host computer system) for said disk boot sector is intercepted
by the Supervisor and said loader sector is supplied to
satisfy the request, the loader sector being executed by the
CPU of the computer system in place of the requested disk boot
sector, said loader sector transferring a code segment (stored

-19-

on a reserved track therefor on the disk platter(s) and referred to in further detail below) into RAM of the CPU of the host computer system for execution thereby; said code segment when executed, providing all required user prompts and communication with the Supervisor required for entry into either "protected" or "unprotected" mode, such that, subsequent to mode selection, said code segment executes the original disk boot sector program which then initiates the process of operating system boot. This modified operating system boot operation will now be explained in further detail with reference to Fig.2 of the drawings which is a flow chart illustrating this operating system boot sequence.

In the normal operation of a computer system, upon switch on of the system (or a request to re-boot the system) the host system central processing unit (CPU) requests the disk boot sector from the boot partition of a disk platter of the hard drive. In the present invention, the Supervisor intercepts any request for the disk boot sector. Upon interception of the disk boot sector request, the Supervisor returns the loader means (namely the virtual "loader sector") stored in the ROM chip 4 in place of the disk boot sector. The host system will be unaware of this change having been made and will execute the loader sector which, in turn, transfers a code segment,

-20-

stored in the storage device, to a RAM in the host computer system. This code segment is stored in a track 8 on the disk platter (or one of the disk platters) which is reserved therefor. This track is accessible only to the Supervisor
5 means, being a track which is outside the area of the disk platter accessible to the host operating system.

The code segment contains code, to be executed by the host system, which issues user prompts and which communicates with
10 the Supervisor, in order to enable the user to set the system in the "protected" mode or "unprotected" mode, as will be described herebelow.

Once the code segment has been transferred to the RAM of the
15 host computer system it is executed thereby so as to, firstly, establish communication with the Supervisor, and then provide a user display screen (known as the HARDWALL banner - HARDWALL is a registered trade mark of Vircon Limited) which prompts the user to select a desired protection mode, namely either
20 "protected" or "unprotected". If the user selects the "protected" mode the code segment then requests a list of dormant partitions from the Supervisor and displays them on the screen of the computer system and prompts the user to select one or more partitions from the list. Once the user has

-21-

selected one or more partitions the code segment informs the Supervisor of this choice. Prior to selecting a partition or partitions, which then become active, the system will previously have been configured in terms of partitions and a level of protection associated with them. These may be established by means of a software utility. In general, there are three types of partition, namely general partitions, read-only partitions and WMR partitions. Typically, a read-only partition and a WMR partition are always available. At the start of a session, when a general partition (or partitions) is selected and made active it is granted full read/write access. The remaining general partitions then become dormant whereby the Supervisor prevents their contents being accessed and hence protects them during that particular user session (which lasts until switch-off or re-boot of the computer system). Read-only partitions are granted read access only, all write commands being prohibited by the Supervisor. The function and features of the Supervisor are disclosed and described in detail in US 5,657,473 (incorporated herein by reference) and will therefore not be repeated here.

In the preferred embodiment, at the stage of the process where the user selects one or more active partitions, the executed code segment will make available to the user one or more

-22-

partitions designated as Write-Many-Recoverable (WMR) partitions. If a write command is issued by the host system (e.g. by a user program) to overwrite any resident information stored in that WMR partition, the updated information is

5 stored elsewhere on the disk platter(s) in a dedicated area thereof, and a (virtual) pointer to the updated information is kept (in the RAM chip 5 of the drive) so the updated information can be accessed as required during the remainder of the session, and wherein a system reset causes the list of

10 pointers to the updated information, and optionally also the updated information itself, to be cleared. Each WMR partition has a Sector Relocation Table (SRT) associated with it containing the (virtual) pointers which define the address of a range of sectors in the WMR partition which have been

15 updated and an address where the updated information is located. This updated information is located in a dedicated area of the disk platter(s) which is accessible only to, and is protected by, the Supervisor. This may be achieved by the dedicated area being disposed in an area of the disk

20 platter(s) to which any access by the host system is denied by the Supervisor, the dedicated area in this manner being effectively "hidden" from the host system. Alternatively, the dedicated area could be disposed outwith the physical area (namely tracks) of the disk platter(s) which is accessible to

-23-

the host operating system, in an area which is accessible only to the Supervisor. The SRT table(s) are stored in the RAM chip 5 of the disk drive 1. The details and implementation of the WMR technique are disclosed and described in detail in EP 0 5 800 135 A1, previously referred to and incorporated herein by reference, and are therefore not described in any further detail herein. It will be appreciated that the WMR facility enables a user to write to the designated WMR partition(s) during a session on the computer system, but each time the 10 computer system is re-booted all changes are erased so as to leave each WMR partition in its original state. Typically, the boot partition will be chosen by the user to be designated a WMR partition.

15 In an alternative WMR technique, also described in EP 0 800 135 A1, if a partition is designated as WMR, in use, if a write command is issued to overwrite (i.e. update) any information stored in a/the WMR partition prior to undertaking said write command said information is copied and stored 20 elsewhere on the storage medium to be copied back to said WMR partition when required. This could be implemented, for example, by a system reset. For the avoidance of doubt, the use of this alternative WMR is method is also intended to be within the scope of the present invention.

The RAM chip 5 is also used to store information regarding the protection state attributed to each partition in the drive at any given time, for example which partitions are active and 5 which are inactive, which are WMR partitions, which are read/write accessible, which are read-only, etc. This information, which can be referred to as a Permission Table, is also stored in the RAM chip 5 of the disk drive 1.

10 Once the active partition(s) have been selected, and any WMR partitions, the code segment transfers the original disk boot sector stored in the disk drive to the host computer system RAM for execution thereby, the executed disk boot sector initiating operating system boot in the host system.

15

If, at the stage where the user is prompted to select "protected" or "unprotected" mode (i.e. "supervised" or "unsupervised"), the user selects "unprotected", the code segment prompts the user to enter a password. The password 20 entered by the user is then transferred to the Supervisor firmware for validation thereby (by matching it against a correct password stored in the ROM chip 4 of the drive 1). A limited number of retries is permitted if the user enters an incorrect password. Once a correct password has been entered

-25-

and validated, the code segment provides the user with the option of requesting to change the password. If such a request is made, the code segment prompts for a new password to be entered twice, the two entered passwords then being transferred to the Supervisor firmware for comparison and storage (in the ROM chip 4 of the drive). The Supervisor then enters the "unprotected" or "unsupervised" mode and the code segment proceeds to transfer the original disk boot sector to the host system RAM for execution thereby in order to initiate operating system boot in the host system.

A more detailed description of the above-described embodiment is not given herein, as this would be within the normal understanding of a person skilled in the art.

15

The embodiment of the present invention includes no physical electronic components that are not present in many commercially available hard disk drives. The invention requires only the following features in the disk drive in order to implement the invention thereon:

memory locations within the Read Only Memory (ROM) chip 4 to contain the firmware code to implement Supervisor functionality (the Supervisor firmware);

-26-

integration of the Supervisor firmware into the existing control firmware of the hard disk drive, ensuring that no interface request is serviced before the Supervisor firmware has checked and validated the request;

5 memory locations with the embedded Random Access Memory (RAM) 5 of the hard disk drive to store the SRT and Permission Table which are created and maintained during each session on the computer system;

memory locations within the ROM for the storage of the 10 password for use in selecting supervised or unsupervised mode; memory locations within the ROM 4 for the storage of the (virtual) loader sector;

sectors on the hard disk drive itself for storage of the code segment which is required to be passed to the computer system 15 and executed during the initial power up and configuration process, said sectors being within one or more reserved tracks on the disk surface which are inaccessible to the host computer system (and any user programs running therein) and accessible only to the Supervisor.

20

It should be noted that the Supervisor firmware is configured to prohibit any access to itself, or alteration to itself, by user commands (issued by a user or user program) which attempt to read, corrupt or modify the Supervisor firmware.

It will be appreciated that, as an alternative to providing the invention in the drive at manufacture thereof, where a hard drive having the necessary features outlined immediately above is provided, the invention could be implemented by loading the Supervisor firmware into the disk drive by means of a software utility program in order to obtain a disk drive which operates in accordance with the present invention. Although the Supervisor firmware will preferably be loaded into the ROM of the drive, it is envisaged that some or all of the Supervisor firmware could be written onto the disk platter(s). In this latter case, any of the Supervisor firmware which is stored on the disk platter(s) will be protected by the Supervisor itself so that a user or user program cannot gain read or write access thereto.

The embodiments of the present invention hereinbefore described are given by way of example only, and it will be appreciated that various modifications thereto will be possible without departing from the scope of the invention.

THIS PAGE BLANK (USPTO)

1/2






fig. 1

THIS PAGE BLANK (USPTO)

2/2
Fig. 2



THIS PAGE BLANK (USPTO)



5/5

FIGURE 5

PCT/GB 99/01433 - 7 MAY '99

FRANK B. DEHN + CO. - 990457B.3

THIS PAGE BLANK (USPTO)